Electrical Characteristics (T_J = 25°C unless otherwise specified)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Off Characteristics						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	I_D = 250μA, V_{GS} = 0V	30	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 30V, V_{GS} = 0V	-	-	1.0	μA
I_{GSS}	Gate-Body Leakage Current	V_{DS} = 0V, V_{GS} = ±20V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	1.0	1.9	2.5	V
$R_{DS(ON)}$	Static Drain-Source ON-Resistance(4)	V_{GS} = 10V, I_D = 30A	-	2.6	3.4	mΩ
		V_{GS} = 4.5V, I_D =20A	-	4.9	6.4	mΩ
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{GS} = 0V, V_{DS} = 15V, f = 1MHz	-	3650	-	pF
C_{oss}	Output Capacitance		-	494	-	pF
C_{rss}	Reverse Transfer Capacitance		-	366	-	pF
Q_g	Total Gate Charge	V_{GS} = 0 to 10V V_{DD} = 30V, I_D = 15A	-	67	-	nC
Q_{gs}	Gate Source Charge		-	11	-	nC
Q_{gd}	Gate Drain("Miller") Charge		-	19	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-On DelayTime	V_{GS} = 10V, V_{DD} = 15V I_D= 30A, R_{GEN} = 3Ω	-	10	-	ns
t_r	Turn-On Rise Time		-	19	-	ns
$t_{d(off)}$	Turn-Off DelayTime		-	50	-	ns
t_f	Turn-Off Fall Time		-	20	-	ns
Drain-Source Diode Characteristics and Max Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	150	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	600	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS} = 0V, I_S = 30A	-	-	1.2	V
trr	Body Diode Reverse Recovery Time	I_F=20A,di/dt=100A/εs	-	18	-	ns
Qrr	Body Diode Reverse Recovery Charge		-	6	-	nC

Notes: 1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature.

2. E_{AS} condition: Starting T_J=25 , V_{DD}=15V, V_G=10V, R_G=25q, L=0.5mH, I_{AS}=29A.

3. R_{dJA} is measured with the device mounted on a 1inch^2 pad of 2oz copper FR4 PCB.

4. Pulse Test: Pulse Width 300εs, Duty Cycle 0.5%.

Package Mechanical Data(TO-252-3L)



Information furnished in this document is believed to be accurate and reliable.
However, Jiangsu JieJie Microelectronics Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.
Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.
Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

is a registered trademark of Jiangsu JieJie Microelectronics Co.,Ltd.
Copyright ©2023 Jiangsu JieJie Microelectronics Co.,Ltd. Printed All rights reserved.