



JOCDA3BB-L5X Series

Rev.A.1.0

) - o#k@u@V

The products are gate driver opto-couplers in LSOP5 and LSOP5W packages. The device consists of an infrared LED optically coupled to an integrated high-gain, high-speed photodetector IC chip. It provides guaranteed performance and specifications at temperature up to 110 . It is physically smaller and compliant with international safety standards for reinforced insulation. It thus provides a smaller footprint solution for applications that require safety standard certification. An internal noise shield provides a guaranteed common-mode transient immunity of ± 35 kV/ μ s. It is ideal for small class IGBT and power MOSFET gate drive. The products are widely used in industrial inverters, IGBT gate drivers, MOSFET gate drivers, induction cooktop and home appliances.

U ° @ 7- ° uyk-o

3A maximum peak output current

High isolation 5000 VRMS

Buffer logic type

Operating temperature range -40°C to 110°C


REACH & RoHS compliance

HBM: H3A; MM: M4; CDM: C3

CQC approved

VDE approved

UL approved



u u

LED	V _{CC} -V _{EE} (Positive Going)	V _{CC} -V _{EE} (Negative Going)	Output
OFF	0-30V	0-30V	Low
ON	0-6.9V	0-5.9V	Low
ON	6.9V-8.7V	5.9V-7.5V	TRANSITION
ON	8.7V-30V	7.5V-30V	HIGHT



(Temperature=25°C)

Parameter		Symbol	Value	Unit
LED	Forward Current	I _F	50	mA
	Peak Forward Current	I _{FP}	1	A
	Reverse Voltage	V _R	6	V
	Power Dissipation	P _D	100	mW
Detector	Output Voltage	V _O	35	V
	Supply Voltage	V _{CC}	35	V
	Power Dissipation	P _C	400	mW
Isolation Voltage		V _{iso}	5000	Vrms
Operating Temperature		T _{opr}	-40~110	
Junction Temperature		T _j	125	
Storage Temperature		T _{stg}	-55~125	
Total Power Dissipation		P _{tot}	500	mW
Soldering Temperature		T _{sol}	260	

V_u : 100μs pulse, 100Hz frequency

V_u : AC for 1minute, R.H.=40~60%

(Temperature=25°C)



High Level Output Voltage	V_{OH}	$I_F=5mA,$ $V_{CC}=10V,$ $I_O=-100mA$	6	8.4	-	V
Low Level Output Voltage	V_{OL}	$V_F=0.8V,$ $V_{CC}=10V,$ $I_O=100mA$	-	0.3	1	V
Threshold Input Current	I_{FLH}	$V_{CC}=15V,$ $V_O=1V$	-	1.2	5	mA
Threshold Input Voltage	V_{FHL}	$V_{CC}=15V,$ $V_O=1V$	0.8	-	-	V
Supply Voltage	V_{CC}	-	10	-	30	V
UVLO Threshold	VUVLO+	$V_O=2.5V,$ $I_F=5mA$	7.5	8.7	9.5	V
	VUVLO-	$V_O=2.5V,$ $I_F=5mA$	7.5	8.4	9.5	V



of @#=@8'oh-#@#@ u@V'

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
-----------	--------	-----------	------	------	------	------

Propagation Delay Time to top	t _{pd}	V _{in} = 0, V _{out} = 1				ns
-------------------------------	-----------------	---	--	--	--	----



k

\

#


Characteristics	Symbol	Min.	Typ.	Max.	Unit
Input On-state Current	$I_{F(ON)}$	6.5	-	10	mA
Input Off-state Voltage	$V_{F(OFF)}$	0	-	0.8	V
Supply Voltage	V_{CC}	10	-	30	V

Operating Frequency

f




U° kM8' U° kM8'



h j	
\ .	j .
None/R	3000 Units/Reel

U° kM8'





#

#

FIG.1: Forward Current vs. Forward Voltage

FIG.2:

FIG.7: Low-level Output Voltage vs. Ambient Temperature






FIG.8: High-level Output Voltage vs. Ambient Temperature

FIG.13: Propagation Delay Time,Pulse Width Distortion vs. Supply Voltage



h) y . . .
 Q\h .




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	7.40		7.80	0.291		0.307
B	3.40		3.80	0.134		0.150
C	0.00		0.20	0.000		0.008
D	1.80		2.20	0.071		0.087
E	8.10		8.70	0.319		0.343
F	0.40		1.00	0.016		0.039
G	9.90		10.50	0.390		0.413
H	0.10		0.30	0.004		0.012
I	1.80		2.40	0.071		0.094
J	0.25		0.55	0.010		0.022
K						




k-# \ U U - V) -) ' \ Q - k U ° d M)

Ø \ h





Ø \ h †








#° kk@k'ù h- 'dh-#@#° u@ Vo')

\ V k'





$k = 70 \pm 10 \mu A/V^2$ $U_{GS} = 0$ $V_{DS} = 10V$



Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.
2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.
3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.
4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.
5. The component has a shelf life of one year when stored under1

3 \$

r o a t a
n