



JST12C-1000SW 12A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST12C-1000SW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST12C-1000SW snubberless triac is especially recommended for use on inductive loads. It can be driven directly through the MCU I/O port. From T2 terminals to external heatsink. Package TO-220C is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T_{stg}	-40-150	
Operating junction temperature range	T_j	-40-125	
Repetitive peak off-state voltage ($T_j=25^\circ\text{C}$)	V_{DRM}	1000	V
Repetitive peak reverse voltage ($T_j=25^\circ\text{C}$)	V_{RRM}	1000	V
RMS on-state current ($T_C=103^\circ\text{C}$)	$I_{T(RMS)}$	12	A
Non repetitive surge peak on-state current (full cycle, $t_p=20\text{ms}$, $T_j=25^\circ\text{C}$)	I_{TSM}		

Peak pulse voltage (Tj=25 ; non-repetitive,off-state;FIG.7)	Vpp	4	kV V4
--	-----	---	-------

ORDERING INFORMATION

J	ST	12	C	-1000	SW
<u>JieJie Microelectronics Co., Ltd.</u>	<u>Triacs</u>				

13100052T091052Fw .

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



