



JST134C-600E 4A TRIAC

Rev. A. 1.1

DESCRIPTION:

The JST134C-600E triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controller. From T2 terminals to external heatsink. Package TO-220C is RoHS compliant.

MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	$T_{stg}$	-40-150	
Operating junction temperature range	$T_j$	-40-125	
Repetitive peak off-state voltage ( $f=25$ )	$V_{DRM}$	600	V
Repetitive peak reverse voltage ( $f=25$ )	$V_{RRM}$	600	V
RMS on-state current ( $T=110$ )	$I_{T(RMS)}$	4	A
Non repetitive surge peak on-state current (full cycle, $t_p=20ms$ , $f=25$ )	$I_{TSM}$	25	A
Non repetitive surge peak on-state current (full cycle, $t_p=16.6ms$ , $f=25$ )		27.5	
$I^2t$ value for fusing ( $t=10ms$ , $T=25$ )	$I^2t$	3.125	$A^2s$
Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ , $f=100Hz$ , $T=125$ )		70	A/s
		40	


ELECTRICAL CHARACTERISTICS (T<sub>C</sub>=25 unless otherwise specified)

---

Symbol	Test Condition	Quadrant	Value	Unit	jwzd
--------	----------------	----------	-------	------	------

---

ORDERING INFORMATION



MARKING Production C




FIG.1 : Maximum power dissipation versus RMS on-state current




FIG.3: Surge peak onstate current versus number of cycles



FIG.2: RMS on-state current versus case temperature




FIG.4: On-state characteristics



ORDERING INFORMATION

Order code	Voltage $V_{DRM}/V_{RRM}$ (V)	IGT (mA)		Package	Base qty. (pcs)	Delivery mode
		-	-			
JST134C-600E	600	10	25	TO-220		

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright ' 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.