

JST25T-800CW 25A TRIAC

Rev.A.1.0

DESCRIPTION:

The JST25T-800CW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in

Peak pulse voltage (T _j =25 ; non-repetitive, off-state; FIG.7)	V _{pp}	2.5	kV
---	-----------------	-----	----

ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol	Test Condition	Quadrant	Value	Unit
I _{GT}	V _D =12V R _L =33	- -	MAX. 35	mA

ORDERING INFORMATION

	J	ST	25	T	-800	CW
JieJie Microelectronics Co., Ltd.		Triacs				

800:V_{DRM} /V_{RRM}

FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature

ORDERING INFORMATION

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}(\text{V})$	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
		H- I- J			
JST25T-800CW	800	35	TG-C(Ins)	10	Tube

Document Revision History

Date	Revision	Changes
Apr.12, 2023	A.1.0	Last updated

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2023 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.