



JST30C-800CW 30A TRIAC

Rev.A.1.1

DESCRIPTION:

The JST30C-800CW triac is suitable for general purpose

AC switching. It can be used as an ON/OFF function in

applications such as heating regulation, induction motor

star0 9 345.84 3925 ()-125 (6.05 0 /(t)2 (abl)16 (e(ar)7 (nd)1 (or)7 (g)9.96 (ed)p (or)h (o (ng)9

Peak pulse voltage ($T_j=25^\circ\text{C}$; non-repetitive, off-state; FIG.7)	V_{pp}	2.5	kV
--	----------	-----	----

ELECTRICAL CHARACTERISTICS (unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	$V_D=12\text{V}$ $R_L=33$	- -	MAX.	35	mA
V_{GT}		- -	MAX.	1.3	V
V_{GD}	$V_D=V_{DRM}$ $T_j=125^\circ\text{C}$ $R_L=3.3\text{k}$	- -	MIN.	0.15	V

I_L I

ORDERING INFORMATION

<u>J</u>	<u>ST</u>	<u>30</u>	<u>C</u>	<u>-800</u>	<u>CW</u>
JieJie Microelectronics Co., Ltd.	Triacs	<u>IT(RMS):30A</u>	<u>C:TO-220C</u>	<u>800:VDRM /VRRM 1800 V</u>	<u>CW:IGT1-3 035 mA</u>

MARKING



FIG.1: Maximum power dissipation versus RMS on-state current




FIG.2: RMS on-state current versus case temperature



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.